

Advances in Underground Pipeline Design, Construction and Management

Jey K. Jeyapalan



| | |
|--|------|
| Chapter 1 | 1-1 |
| Introduction | |
| Chapter 2 | 2-1 |
| Design, Installation, and Pipe Performance: Inter-Dependence | |
| 2.1 General | 2-1 |
| 2.2 Pipeline Terminology | 2-1 |
| 2.2.1 Definitions | 2-1 |
| 2.2.1.1 Foundation | 2-1 |
| 2.2.1.2 Bedding | 2-2 |
| 2.2.1.3 Haunching | 2-2 |
| 2.2.1.4 Backfill | 2-2 |
| 2.2.1.5 Cover | 2-2 |
| 2.2.1.6 Excavation | 2-2 |
| 2.2.1.7 Pipe Strength | 2-2 |
| 2.2.1.8 Pipe Stiffness | 2-2 |
| 2.3 Special Considerations in Construction by Cut and Cover | 2-3 |
| 2.3.1 Introduction | 2-3 |
| 2.3.2 Inter-Dependence of Design, Installation, and Pipe Performance | 2-4 |
| 2.3.3 Other Considerations | 2-4 |
| 2.4 Special Considerations in Construction by Conventional Tunneling | 2-5 |
| 2.5 Special Considerations in Construction by Microtunneling | 2-5 |
| 2.6 Design Loads | 2-6 |
| 2.6.1 Trench Condition | 2-7 |
| 2.6.2 Positive Projection Conduit | 2-10 |
| 2.6.3 Negative Projection Conduit and Induced Ditch Conduit | 2-12 |
| 2.6.3.1 Negative Projection Conduit | 2-12 |
| 2.6.3.2 Induced Trench Conduit | 2-12 |
| 2.7 Basic Design Calculations | 2-13 |
| 2.7.1 Loads on Pipe-Design Example 1 | 2-14 |
| 2.7.2 Deflection in Flexible Pipe-Design Example 2 | 2-15 |
| 2.7.3 Wall Crushing-Design Example 3 | 2-17 |
| 2.7.4 Bending Stress and Strain-Design Example 4 | 2-18 |
| 2.7.5 Buckling-Design Example 5 | 2-21 |
| 2.8 Summary | 2-26 |
| Chapter 3 | 3-1 |
| Geotechnical Design Parameters | |
| 3.1 Background | 3-1 |
| 3.2 Importance of Soil in Pipe-Soil System Design | 3-5 |
| 3.3 Challenges of the Underground | 3-5 |
| 3.4 Geotechnical Baseline Investigation | 3-6 |
| 3.5 Need for Laboratory Tests | 3-8 |
| 3.6 Typical Laboratory Tests | 3-9 |
| 3.6.1 Visual Classification | 3-9 |
| 3.6.2 Moisture Contents | 3-9 |
| 3.6.3 Atterberg Limits | 3-9 |
| 3.6.4 Grain Size Analyses | 3-10 |
| 3.6.5 Unit Weights | 3-10 |
| 3.6.6 Blow Count and Relative Density of Cohesionless Soils | 3-11 |
| 3.6.7 Blow Count and Unconfined Compressive Strength of Clays | 3-11 |
| 3.7 Need for Shear Strength Properties | 3-11 |
| 3.7.1 Field Shear Strength Tests | 3-12 |
| 3.7.2 Laboratory Shear Strength Tests | 3-12 |
| 3.7.3 Direct Shear Tests | 3-12 |
| 3.7.4 Triaxial Shear Tests | 3-12 |
| 3.8 Compaction Tests of Bedding and Backfill | 3-13 |
| 3.9 Appropriate Installation Specifications | 3-14 |
| 3.10 Geotechnical Design Summary Report | 3-15 |
| 3.11 Soil-Pipe Interaction | 3-18 |

| | |
|--|------|
| 3.12 Soil Stiffness | 3-19 |
| 3.13 Problems with Howard's Work on E' | 3-20 |
| 3.14 Modulus of Soil Reaction, E' | 3-25 |
| 3.15 Selection of E' for Trenchless | 3-27 |
| 3.16 Soil Migration | 3-29 |
| 3.17 Recommendations | 3-29 |
| Chapter 4 | 4-1 |
| Pipe Manufacturing and Material Properties | |
| 4.1 Plastic Pipes | 4-1 |
| 4.1.1 Introduction | 4-1 |
| 4.1.2 Molecular Structure and Strength | 4-2 |
| 4.1.3 Polyethylene Pipes | 4-2 |
| 4.1.4 Polypropylene Pipes | 4-4 |
| 4.1.5 Polyvinyl Chloride Pipes | 4-4 |
| 4.1.6 HDPE Profiled Wall Pipe | 4-5 |
| 4.1.7 Closed Profile Walled High Density Polyethylene | 4-6 |
| 4.1.8 Open Profile Walled High Density Polyethylene | 4-6 |
| 4.1.9 Polyester Concrete Pipe | 4-6 |
| 4.2 Fiberglass Pipes | 4-6 |
| 4.2.1 FRP Pipe Manufacturing | 4-8 |
| 4.2.1.1 Filament Winding | 4-10 |
| 4.2.1.2 Reciprocal Method | 4-10 |
| 4.2.1.3 Continuous Method | 4-10 |
| 4.2.1.4 Multiple Mandrel Method | 4-10 |
| 4.2.1.5 Ring and Oscillating Mandrel Method | 4-11 |
| 4.2.1.6 Centrifugally Casting Method | 4-11 |
| 4.2.1.7 Pre-formed Glass Reinforcement Sleeve Method | 4-11 |
| 4.2.1.8 Chopped Glass Reinforcement Method | 4-11 |
| 4.2.2 Centrifugally Cast Fiberglass (CEN) Pipe | 4-11 |
| 4.2.3 Continuous Filament Winding (CFW) Pipe | 4-12 |
| 4.2.4 Discontinuous Helical Filament Winding (DHFV) Pipe | 4-12 |
| 4.3 Concrete Pipes | 4-13 |
| 4.3.1 Precast Reinforced Concrete Pipe | 4-17 |
| 4.3.2 Cast in Place Concrete Pipe | 4-18 |
| 4.3.3 Precast Reinforced Concrete Boxes | 4-18 |
| 4.3.4 Cast in Place Concrete Boxes | 4-18 |
| 4.3.5 Reinforced Silica Fumed Concrete Pipe | 4-18 |
| 4.3.6 Design of Concrete Pipe | 4-18 |
| 4.4 Ductile Iron Pipes | 4-20 |
| 4.5 Steel Pipes | 4-21 |
| 4.5.1 Background | 4-21 |
| 4.5.2 Manufacture of Steel Pipes | 4-22 |
| 4.6 Clay Pipes | 4-23 |
| 4.6.1 Background | 4-23 |
| 4.6.2 Field Supporting Strength | 4-23 |
| 4.6.3 Supporting Strength in Trench Conditions | 4-24 |
| 4.6.4 Principles of Concrete Bedding Design | 4-25 |
| 4.6.4.1 Delay Backfilling the Trench | 4-25 |
| 4.6.4.2 Delay Consolidation of the Trench | 4-25 |
| 4.6.4.3 Accelerate the Early Strength of the Concrete | 4-25 |
| 4.6.4.4 Avoid Shear at Joints and Connections | 4-26 |
| 4.6.4.5 Use of Steel Reinforcing | 4-26 |
| 4.6.4.6 Pipe Flotation | 4-26 |
| 4.6.5 Rigid Pipe Strength in Europe versus America | 4-26 |
| 4.7 Alternate Pipe Materials for Pipeline Projects | 4-26 |
| 4.7.1 Introduction | 4-26 |
| 4.7.2 Selection Criteria | 4-27 |
| 4.7.3 Availability | 4-28 |

| | |
|--|------|
| 4.7.4 Corrosion Resistance | 4-28 |
| 4.7.5 Abrasion Resistance | 4-29 |
| 4.7.6 Hydraulic Roughness and Flow Capacity | 4-30 |
| 4.7.7 Structural Strength | 4-30 |
| 4.7.8 Structural Stiffness | 4-30 |
| 4.7.9 First Time Pipe Cost | 4-31 |
| 4.7.10 Operation and Maintenance Cost | 4-31 |
| 4.7.11 Bedding Requirements and Options | 4-31 |
| 4.7.12 Handling and Shipping | 4-31 |
| 4.7.13 Repair of Damaged Pipe | 4-32 |
| 4.7.14 Ease of Future Connections and Expansion | 4-32 |
| 4.7.15 Types and Effectiveness of Joints | 4-33 |
| 4.7.16 Speed of Construction | 4-34 |
| 4.7.17 Track Record | 4-34 |
| 4.7.18 Basis and Establishment of a Scoring System for Ranking | 4-34 |
| 4.7.19 Ranking of Pipe Materials | 4-35 |
| 4.8 Applicable ASTM and Other Standards | 4-35 |
| 4.8.1 Comparison of Standards | 4-36 |
| 4.8.2 American Standards | 4-36 |
| 4.8.2.1 Product Specifications | 4-36 |
| 4.8.2.1.1 Aluminum Alloy Pipe | 4-36 |
| 4.8.2.1.2 Asbestos-Cement Pipe | 4-37 |
| 4.8.2.1.3 Concrete Pipe | 4-37 |
| 4.8.2.1.4 Ductile Iron Pipe | 4-38 |
| 4.8.2.1.5 Fiberglass Pipe | 4-39 |
| 4.8.2.1.6 Plastic Pipe | 4-39 |
| 4.8.2.1.7 Steel Pipe | 4-40 |
| 4.8.2.2 Recommended Practices | 4-41 |
| 4.8.2.3 Installation | 4-41 |
| 4.8.2.4 Test Methods | 4-42 |
| 4.8.2.4.1 Tensile Properties | 4-42 |
| 4.8.2.4.2 Compressive Properties | 4-42 |
| 4.8.2.4.3 Bending Properties | 4-42 |
| 4.8.2.4.4 Long Term Internal Pressure Strength | 4-42 |
| 4.8.2.4.5 Pipe Stiffness | 4-42 |
| 4.8.2.4.6 External Pressure | 4-42 |
| 4.8.2.4.7 Chemical Resistance | 4-42 |
| 4.8.3 Australian and New Zealand Standards | 4-43 |
| 4.8.3.1 Pipes in General | 4-43 |
| 4.8.3.2 Coatings and Linings | 4-43 |
| 4.8.3.3 Product Specifications and Classifications | 4-44 |
| 4.8.3.3.1 Iron and Steel Pipe | 4-44 |
| 4.8.3.3.2 Concrete Pipe | 4-44 |
| 4.8.3.3.3 Plastic Pipe | 4-45 |
| 4.8.3.3.4 Vitrified Clay Pipe | 4-47 |
| 4.8.3.4 Installation | 4-47 |
| 4.8.4 Standards by Other Groups and Countries | 4-48 |
| 4.8.4.1 International Standard Writing Bodies | 4-48 |
| 4.8.4.2 Pipe Trade Associations and Professional Societies | 4-48 |
| 4.8.4.3 Trade Magazines | 4-49 |
| 4.8.5 Design of Underground Pipelines by Following Standards | 4-49 |
| Chapter 5 | 5-1 |
| Unified Design of Buried Pipes | |
| 5.1 Introduction | 5-1 |
| 5.1.1 Design Terminology | 5-3 |
| 5.1.2 Nomenclature | 5-4 |
| 5.2 Design Conditions | 5-6 |
| 5.2.1 Head Losses | 5-6 |

| | |
|--|------|
| 5.2.2 Surge Pressures | 5-6 |
| 5.2.3 Basic Design Conditions | 5-6 |
| 5.3 Pipe Properties | 5-6 |
| 5.4 Installation Parameters | 5-7 |
| 5.5 Design Procedure | 5-7 |
| 5.6 Design Calculations and Requirements | 5-8 |
| 5.6.1 Internal Pressure | 5-8 |
| 5.6.1.1 Pressure Class, P_c | 5-8 |
| 5.6.1.1.1 Hydrostatic Design Basis | 5-8 |
| 5.6.1.1.2 Temperature and Service Life | 5-8 |
| 5.6.1.1.3 Design Factors | 5-9 |
| 5.6.1.2 Working Pressure, P_w | 5-9 |
| 5.6.1.3 Surge Pressure, P_s | 5-9 |
| 5.6.1.3.1 Calculated Surge Pressure | 5-9 |
| 5.6.1.3.2 Surge Allowance | 5-10 |
| 5.6.2 Ring Bending | 5-10 |
| 5.6.2.1 Shape Factor, D_f | 5-10 |
| 5.6.2.2 Long-Term Ring-Bending Strain, S_b | 5-10 |
| 5.6.2.3 Bending Design Factor | 5-11 |
| 5.6.3 Deflection | 5-11 |
| 5.6.3.1 Deflection Calculations | 5-12 |
| 5.6.3.2 Deflection Prediction | 5-12 |
| 5.6.3.3 Deflection Lag Factor, D_l | 5-13 |
| 5.6.3.4 Bedding Coefficient, K_x | 5-13 |
| 5.6.3.5 Vertical Soil Load on the Pipe, W_c . | 5-13 |
| 5.6.3.6 Live Loads on the Pipe, W_L | 5-13 |
| 5.6.3.7 Pipe Stiffness, PS | 5-14 |
| 5.6.3.8 Modulus of Soil Reaction, E' | 5-15 |
| 5.6.3.9 E' Special Cases | 5-15 |
| 5.6.4 Combined Loading | 5-16 |
| 5.6.5 Buckling | 5-19 |
| 5.6.5.1 Buckling Theory | 5-19 |
| 5.6.5.2 Buckling Calculations | 5-20 |
| 5.6.5.3 Normal Pipe Installations | 5-21 |
| 5.6.5.4 Special Cases | 5-21 |
| 5.7 Axial Loads | 5-21 |
| 5.8 Special Design Considerations | 5-21 |
| 5.9 Design Examples | 5-22 |
| 5.9.1 Design Example 1 - Stress Basis | 5-22 |
| 5.9.2 Design Example 2 - Strain Basis | 5-30 |
| 5.9.3 Design Example 3 - Strain Basis | 5-37 |
| Chapter 6 | |
| Australian Design of Buried Pipes | 6-1 |
| 6.1 Introduction | 6-1 |
| 6.2 Design of Rigid Pipes | 6-1 |
| 6.2.1 Nomenclature | 6-1 |
| 6.2.2 Vertical Working Loads Due to Dead Loads | 6-2 |
| 6.2.2.1 Trench Condition | 6-2 |
| 6.2.2.2 Embankment Condition-Positive Projection | 6-3 |
| 6.2.2.3 Embankment Condition-Negative Projection | 6-3 |
| 6.2.2.4 Multiple Pipes | 6-3 |
| 6.2.2.5 Jacked/Bored Pipes | 6-3 |
| 6.2.3 Superimposed Dead Loads | 6-3 |
| 6.2.4 Vertical Working Loads Due to Live Loads | 6-4 |
| 6.2.4.1 Road Vehicle Loads | 6-4 |
| 6.2.4.1.1 Distribution of Wheel Loads | 6-4 |
| 6.2.4.1.2 NAASRA Vehicle Loads | 6-5 |
| 6.2.4.1.3 Other Road Vehicles | 6-5 |

| | |
|--|------|
| 6.2.4.2 Railway Loads | 6-6 |
| 6.2.4.3 Aircraft Loads | 6-6 |
| 6.2.4.4 Construction and Other Equipment Loads | 6-6 |
| 6.2.5 Internal Water Loads | 6-6 |
| 6.2.6 Pipe Support | 6-6 |
| 6.2.6.1 Type-U Support | 6-6 |
| 6.2.6.2 Type-H Support | 6-7 |
| 6.2.6.3 Type-HS Support | 6-8 |
| 6.2.7 Bedding Factors and Test Loads | 6-9 |
| 6.2.7.1 Bedding Factor | 6-9 |
| 6.2.7.2 Test Loads for Unreinforced Gravity Pipes | 6-10 |
| 6.2.7.3 Test Loads for Reinforced Gravity Pipes | 6-10 |
| 6.2.7.4 Test Loads for Reinforced Pipes with Internal Pressure | 6-11 |
| 6.3 Design of Flexible Pipes | 6-11 |
| 6.3.1 Nomenclature | 6-11 |
| 6.3.2 Properties of Pipe | 6-13 |
| 6.3.2.1 Ring Bending Stiffness | 6-13 |
| 6.3.3 Pipe Embedment Support | 6-14 |
| 6.3.3.1 Embedment Geometry | 6-14 |
| 6.3.3.2 Embedment Materials and Compaction | 6-14 |
| 6.3.4 Design Working Loads | 6-16 |
| 6.3.4.1 Dead Loads due to Embankment/Trench Fill | 6-16 |
| 6.3.4.2 Dead Loads due to Superimposed Dead Loads | 6-17 |
| 6.3.4.3 Superimposed Live Loads | 6-17 |
| 6.3.4.4 Internal Pressure | 6-19 |
| 6.3.4.5 External Hydrostatic Loads | 6-19 |
| 6.3.4.6 Mass of the Contents of the Pipe | 6-19 |
| 6.3.5 Design | 6-19 |
| 6.3.5.1 Long Term Design Basis | 6-19 |
| 6.3.5.2 Deflection | 6-19 |
| 6.3.5.3 Strength | 6-20 |
| 6.3.5.3.1 Long Term Ring Bending Strain | 6-20 |
| 6.3.5.3.2 Internal Pressure | 6-20 |
| 6.3.5.3.3 Combined Loading | 6-20 |
| 6.3.5.4 Buckling | 6-21 |
| Chapter 7 | 7-1 |
| German Design of Buried Pipes | |
| 7.1 Introduction | 7-1 |
| 7.2 ATV Design and Terminology | 7-3 |
| 7.3 ATV Design Calculations | 7-5 |
| 7.4 Calculation of Vertical and Horizontal Earth Loads on the Pipe | 7-6 |
| 7.5 Factors of Safety | 7-14 |
| 7.6 Checking for Bearing Capacity of Pipe Foundation | 7-15 |
| 7.7 Bending Moments and Axial Forces | 7-18 |
| 7.8 Deflection Check | 7-18 |
| 7.9 Buckling | 7-18 |
| 7.10 Design Examples | 7-22 |
| 7.10.1 Example 1 | 7-23 |
| 7.10.2 Example 2 | 7-25 |
| Chapter 8 | |
| Design of Prestressed Concrete Cylinder Pipes | 8-1 |
| 8.1 Introduction | 8-1 |
| 8.2 Historical Overview of PCCP | 8-2 |
| 8.3 PCCP Design Concepts in the Old Methods | 8-4 |
| 8.3.1 PCCP Design: Method A | 8-4 |
| 8.3.2 PCCP Design: Method B | 8-5 |
| 8.3.3 Differences in Standard AWWA C304-99 | 8-5 |
| 8.3.4 PCCP Design Using C304 Standard | 8-5 |

| | |
|---|-------|
| 8.4 Details in AWWA C304-99 | 8-8 |
| 8.4.1 Introduction | 8-8 |
| 8.4.2 Serviceability Limit State | 8-11 |
| 8.4.3 Elastic Limit State | 8-12 |
| 8.4.4 Strength Limit State | 8-12 |
| 8.4.5 Notations | 8-12 |
| 8.4.6 Loads and Internal Pressures | 8-15 |
| 8.4.7 Load and Internal Pressure Combinations | 8-15 |
| 8.4.8 Moments and Thrusts | 8-15 |
| 8.4.9 Stresses from Prestressing | 8-16 |
| 8.4.10 Modular Ratios | 8-18 |
| 8.4.11 Design Creep Factor and Shrinkage Strain for Buried Pipe | 8-19 |
| 8.4.12 Wire Relaxation Factor | 8-19 |
| 8.13 Criteria for Limit State Loads and Pressures | 8-20 |
| 8.13.1 Serviceability Limit States Design Criteria | 8-20 |
| 8.13.2 Elastic Limit States Design Criteria | 8-20 |
| 8.13.3 Strength Limit States Design Criteria | 8-20 |
| 8.13.4 Calculation of Limit State Loads and Pressures | 8-21 |
| 8.14 Design Examples | 8-23 |
| 8.14.1 Design of LCP Using the Design Tables | 8-23 |
| 8.14.2 Design of ECP Using Hand Computations | 8-24 |
| 8.14.2.1 Design Parameters | 8-24 |
| 8.14.2.2 Maximum and Minimum Wire Area | 8-25 |
| 8.14.2.3 State of Stress Calculations | 8-25 |
| 8.14.2.4 Minimum Prestressing Wire Area | 8-26 |
| 8.14.2.5 Stress from Prestressing for Final Area | 8-27 |
| 8.14.2.6 Serviceability at Full Pipe Circumference | 8-27 |
| 8.14.2.7 Serviceability at Invert/Crown | 8-28 |
| 8.15 Shortcomings of ACPPA's Software | 8-28 |
| 8.16 Spreadsheet Implementation of AWWA C-304-99 | 8-28 |
| 8.17 Summary | 8-30 |
| Chapter 9 | 9-1 |
| Unified Approach to Thrust Restraint Design | 9-1 |
| 9.1 Introduction | 9-1 |
| 9.2 Review of Current Design Methodology | 9-1 |
| 9.2.1 Thrust Block Design | 9-1 |
| 9.2.2 Restrained Joint System Design | 9-3 |
| 9.3 Unified Design Philosophy | 9-5 |
| 9.4 Determination of Soil Parameters | 9-7 |
| 9.5 Design Steps | 9-7 |
| 9.6 Design Example | 9-8 |
| 9.7 Summary | 9-9 |
| Chapter 10 | 10-1 |
| Trenchless Technology | 10-1 |
| 10.1 Introduction | 10-1 |
| 10.2 Pipe Ramming | 10-1 |
| 10.3 Directional Drilling | 10-1 |
| 10.4 Microtunneling | 10-1 |
| 10.4.1 Microtunneling Method, Options, and Applicability | 10-3 |
| 10.4.2 Tunneling Vs Microtunneling | 10-4 |
| 10.4.3 Microtunneling | 10-4 |
| 10.4.4 Microtunnel Staging Areas | 10-5 |
| 10.4.5 Shaft Excavation and Support | 10-5 |
| 10.4.6 Starter and Receiver Pit Sizing | 10-6 |
| 10.4.7 Microtunneling Equipment/Method Selection | 10-7 |
| 10.5 Pipe-Soil Interaction Design Considerations in Trenchless Projects | 10-7 |
| 10.5.1 Geotechnical Considerations | 10-8 |
| 10.5.2 Design Loadings | 10-10 |

| | |
|---|-------|
| 10.5.3 Available Pipe Materials | 10-11 |
| 10.6 Design of Trenchless Pipe Soil System | 10-12 |
| 10.6.1 Jacking Loads | 10-13 |
| 10.6.2 Design of Pipe Joints | 10-13 |
| 10.6.3 Design of Starting and Target Pits | 10-13 |
| 10.6.4 Contractual Considerations | 10-14 |
| 10.7 Summary | 10-14 |
| | |
| Chapter 11 | 11-1 |
| Pipe Rehabilitation and Market Potential | |
| 11.1 Introduction | 11-1 |
| 11.2 Collection System Evaluation Methods | 11-2 |
| 11.2.1 Preliminary System Evaluation | 11-2 |
| 11.2.2 Assessing the Infiltration and Inflow Condition | 11-3 |
| 11.2.3 Assessing the Structural Condition | 11-3 |
| 11.2.4 Assessing the Hydraulic Condition | 11-4 |
| 11.3 Municipal Sewer Market | 11-4 |
| 11.3.1 Mainline Renovation | 11-4 |
| 11.3.2 Considerations in Selection of Suitable Technology | 11-5 |
| 11.3.3 Cleaning | 11-6 |
| 11.3.4 Root Control and Removal | 11-6 |
| 11.3.5 Coatings | 11-6 |
| 11.3.6 Point Repairs | 11-7 |
| 11.3.7 Chemical Grouting | 11-7 |
| 11.3.8 Cured in Place Pipes | 11-8 |
| 11.3.9 Fold and Formed Pipes | 11-9 |
| 11.3.10 Directional Drilling | 11-10 |
| 11.3.11 Robotic Repairs | 11-10 |
| 11.3.12 Fill and Drain Methods | 11-10 |
| 11.3.13 Slip Linings | 11-11 |
| 11.3.13.1 Continuous Pipes | 11-11 |
| 11.3.13.2 Discrete Pipes | 11-11 |
| 11.3.13.3 Swaged Pipes | 11-11 |
| 11.3.13.4 Spiral Wound Pipes | 11-12 |
| 11.3.13.5 Segmented Linings | 11-12 |
| 11.3.14 Pipe Bursting | 11-12 |
| 11.3.15 Microtunneling | 11-12 |
| 11.3.16 Pipe Ramming | 11-13 |
| 11.4 Sewer Manhole Rehabilitation | 11-13 |
| 11.5 Sewer Lateral Renovation | 11-13 |
| 11.6 Municipal Sewer Mainline Market Volume | 11-13 |
| 11.7 Municipal Sewer Manhole Market Volume | 11-14 |
| 11.8 Potable Water Market | 11-16 |
| 11.9 National Water Pipe Network | 11-18 |
| 11.10 Typical Water System | 11-19 |
| 11.11 Technologies for Water Pipe Renovation | 11-19 |
| 11.11.1 Nonstructural Lining Systems | 11-20 |
| 11.11.2 Semi-Structural Lining Systems | 11-20 |
| 11.11.3 Structural Renovation Systems | 11-20 |
| 11.12 Potable Water Market Volume | 11-21 |
| 11.13 Gas Market | 11-22 |
| 11.14 Gas Market Volume | 11-22 |
| 11.14.1 Transmission Pipelines | 11-22 |
| 11.14.2 Distribution Pipelines | 11-22 |
| 11.15 Crude Oil Market | 11-23 |
| 11.16 Crude Oil and Product Market Volume | 11-23 |
| 11.17 Industrial Market | 11-22 |
| 11.18 Industrial Market Volume | 11-23 |

| | |
|---|-------|
| 11.19 Cost of Renovation Processes | 11-24 |
| 11.20 Summary | 11-24 |
| Chapter 12 | 12-1 |
| Coatings and Linings Selection | |
| 12.1 Introduction | 12-1 |
| 12.2 Dielectric Coatings | 12-1 |
| 12.2.1 Epoxy | 12-2 |
| 12.2.2 Coal Tar Enamel | 12-2 |
| 12.2.3 Coal Tar Epoxy / Coal Tar Urethane | 12-3 |
| 12.2.4 Urethane | 12-3 |
| 12.2.5 Tapes | 12-4 |
| 12.2.6 Extruded Plastics | 12-5 |
| 12.3 Cement Mortar | 12-5 |
| 12.4 Metallic | 12-5 |
| 12.5 Specification | 12-6 |
| 12.6 Summary | 12-7 |
| Chapter 13 | 13-1 |
| Quality Assurance/Quality Control (QA/QC) Program | |
| 13.1 Objective | 13-1 |
| 13.2 Responsibility | 13-1 |
| 13.3 Quality Assurance Program | 13-1 |
| 13.4 Quality Control Program | 13-2 |
| 13.5 Special QA/QC Requirements for Pipeline Projects | 13-3 |
| 13.6 Level of Inspection Required at the Pipe Plant | 13-3 |
| 13.7 Level of Inspection Required During Construction | 13-4 |
| 13.8 Review of Sample Specifications | 13-4 |
| Chapter 14 | 14-1 |
| Remaining Life for Pipeline Asset Management | |
| 14.1 Introduction | 14-1 |
| 14.2 Inventory of our Assets | 14-1 |
| 14.3 Steps in Reliability Analyses | 14-3 |
| 14.4 Weibull and Normal Probability Distributions | 14-4 |
| 14.5 Typical Results from Reliability Analyses | 14-6 |
| 14.6 Three Case Histories | 14-6 |
| 14.6.1 Case History 1 Using Weibull PDF | 14-6 |
| 14.6.2 Case History 2 Using Normal PDF | 14-7 |
| 14.6.3 Case History 3 Using Normal PDF | 14-8 |
| 14.7 Recommendations | 14-8 |
| Chapter 15 | 15-1 |
| Future Outlook | |
| 15.1 Introduction | 15-1 |
| 15.2 Financial Drivers | 15-2 |
| 15.3 Global Picture of Water and Wastewater Industry | 15-2 |
| 15.4 Global Picture of Pipe Networks | 15-6 |
| 15.5 Driver 1: Desire to do More with Less Money | 15-7 |
| 15.6 Driver 2: Sharing Space and Networks for Multiple Functions | 15-8 |
| 15.7 Driver 3: Innovation in Network Means and Methods | 15-10 |
| 15.8 Driver 4: Innovation in Inspection and Transport Tools | 15-11 |
| 15.9 Driver 5: Use of Automation to Solve Shortfall in Human Skills | 15-13 |
| 15.10 Driver 6: Condition Assessment Based Network Management | 15-14 |
| 15.11 Driver 7: Data Management to Set Funding Priorities | 15-14 |
| 15.12 Where is the Money? | 15-15 |
| 15.13 Final Thoughts | 15-15 |
| References | R-1 |
| Appendices | |
| Appendix 1: Excel Sheet for Selection of Site Specific E' Values | A-1 |
| Appendix 2: Excel Sheet for Design of Gravity FRP Pipe | A-2 |
| Appendix 3: Excel Sheet for Design of Pressure HDPE Pipe | A-3 |

| | |
|--|------|
| Appendix 4: Excel Sheet for German Design of Gravity Concrete Pipe | A-4 |
| Appendix 5: Excel Sheet for Checking PCCP for Compliance with AWWA C304 | A-5 |
| Appendix 6: Excel Sheet for Checking Ductile Iron Pipe in GASB 34 Assessment | A-6 |
| Appendix 7: Sample Specifications for Gravity FRP Pipe | A-7 |
| Appendix 8: Sample Specifications for Gravity HDPE Pipe | A-8 |
| Appendix 9: Sample Specifications for Bedding and Backfill | A-9 |
| Appendix 10: Sample Specifications for Polymer Concrete Pipe | A-10 |